



# LF10 Access Control Device Kit



## LF10 Access Control Device

### Features

- Communication: TCP/IP, USB-host
- Standard advanced access control function to ensure the safe of working environment
- Support for multiple validation methods,demonstrating safety and efficiency

### Specification

Display	2.4" TFT Color Screen
User Capacity	1,500 (optional card:5,000)
FingerPrint Capacity	1,500
Card Capacity	5,000(Optional) ID /Mifare card
Transaction Capacity	80,000
Power Supply	DC 12V 1.5A
Communication	TCP/IP, USB-host
Standard Function	Record Checking, Automatic Status Switch, Advanced Access Control, Wired doorbell, Wiegand Out
Operating Temperature	0 °C- 45 °C
Operating Humidity	20%-80%
Dimensions	83*180.09*33.2mm
Software	ZKBioAccess



## LM-2805 Electromagnetic Lock

### Features

- Can withstand 200kg-220kg closing force;
- U, L, Z, ZL mounting brackets are available;
- Can be installed in metal doors, wooden doors and glass doors;
- With signal feedback function;

### Specification

Input voltage	DC12V
Working current	480m A±5 %
Tensile force range	200kg±5 %
Weight	1.77kg
Lock body size	250x 47 x 25.5mm
Iron plate size	180x 38x 11mm
Interface Description	V + - positive power supply; V - - negative power supply; Feedback signal output: NO/COM/NC



### LMB-280U U

For frameless glass doors  
Size: 180\*43\*28 mm

\* This lock bracket is included in the package and do not need to be purchased separately.